## **EUROPEAN PATENT OFFICE**

## Patent Abstracts of Japan

**PUBLICATION NUMBER** 

03065348

**PUBLICATION DATE** 

20-03-91

APPLICATION DATE

04-08-89

APPLICATION NUMBER

01203323

APPLICANT: MATSUSHITA ELECTRIC IND CO LTD;

**INVENTOR** 


YAMAMORI SEIJI;

INT.CL.

B41J 2/015

TITLE

**INK JET HEAD** 



## ABSTRACT:

PURPOSE: To make compact an ink jet head by providing opening/closing means provided in an ink passage for coupling an ink vessel to an ink discharge port, and means for pressurizing ink by pressure gas, and forming the opening/closing means of a shutter member having an opening, and a shape memory alloy for driving the shutter member in response to a record signal.

CONSTITUTION: After ink is filled in a whole ink passage to an ink discharge port 3, pressure ink is supplied to an ink passage 110 at the ink reservoir side from a shutter member 8. When image signals 6 are applied to both ends of a shape memory alloy member 7, the member 7 us heated, and when it reaches to a martensite transition point, it tends to return to its original shape, thereby pulling up the member 8. In this case, when a pinhole 10 provided at the member 8 reaches the passage 110, the pressure ink is discharged from the port 3. Then, after the signal is applied, the member 7 is cooled by the member 7, and when it is cooled to a martensite transition point or lower, the member 8 is returned by the recoiling force of an elastic member 9 to close the pinhole 10. Since, many nozzles each having simple structure are arranged in high density the structure is simplified and made compact.

COPYRIGHT: (C)1991, JPO& Japio